

THERMONUCLEAR TOKAMAK PANEL REPORT

The Thermonuclear Tokamak Panel, summoned by Dr. R. Pellat, High Commissioner of C.E.A., to evaluate the physics basis of the ITER-FEAT and IGNITOR experimental proposals, met in Paris on the 25th and 26th of November 1999. The designated panel members were:

- Prof. James D. Callen, University of Wisconsin, Madison, WI, USA
- Dr. Geoffrey Cordey, JET, Abingdon, UK
- Dr. Otto Gruber, ASDEX U, Max Planck Institut, Garching bei Muenchen, Germany
- Prof. Wendell Horton, IFS, The University of Texas at Austin, TX, USA
- Dr. Jean Jacquinet, Director of JET, Abingdon, UK (now Director of DRFC, C.E.A., Cadarache, France)
- Prof. Guy Laval, Chairman, Ecole Polytechnique, Paris, France
- Prof. Jean-Francois Luciani, Ecole Polytechnique and C.E.A., Paris, France
- Prof. Franco Porcelli, Politecnico di Torino, Italy

A ninth panel member, Dr. Oleg Pogutse of JET, could not take part in the panel discussions.

On the first day of the meeting, the panel members heard a presentation of the IGNITOR project by Prof. Bruno Coppi of the Massachusetts Institute of Technology, Cambridge, USA, and a presentation of the ITER-FEAT project by Prof. Karl Lackner of the Max Planck Institut and Dr. David Campbell of EFDA, both from Garching bei Muenchen, Germany.

On the second day, the eight panel members discussed the physics basis of the two proposals, their expected performances and their contribution to a reactor-oriented strategy. At the end of the second day, initial conclusions were reached and presented to the High Commissioner.

Several key physics issues were discussed at the meeting. Some of these issues, such as the problem of plasma transport and confinement, are not fully understood. The panel members agreed that a common methodology and common guidelines should be agreed to evaluate the different proposals, and that this task would be best carried out by a dedicated study group. The High Commissioner himself, after he was briefed about the preliminary conclusions reached by the panel members, encouraged work to resolve discrepant points of view. It was agreed that a panel report would be issued that presents as closely as possible the common view of the panel members on the two experimental proposals under consideration. To that objective, an intense activity was initiated after the two-day meeting in Paris,

which involved not only the eight panel members, but also a number of colleagues in the scientific fusion community who helped with comments, suggestions and sometimes actual work. The contribution of these colleagues is acknowledged at the end of this report.

This report is organised as follows. The goals and the parameters of the two proposals, IGNITOR and ITER-FEAT, are presented in Sec. I, together with a discussion of the significance of thermonuclear ignition. Section II presents a physics assessment of the IGNITOR proposal. Section III presents a physics assessment of ITER-FEAT. Conclusions are presented in Sec. IV and recommendations are given in Sec. V.

1. ITER-FEAT AND IGNITOR IN THE FUSION PROGRAM

The main parameters of the two devices under consideration are presented in Table I. It should be made clear from the beginning that the two experimental proposals have different goals.

The goals of the ITER-FEAT experiment¹ are (1) to achieve an extensive burn ($\tau_{\text{burn}} > 100 \tau_E$) in inductively driven plasmas with a thermonuclear gain parameter $Q = (P_{\text{fus}}/P_{\text{in}})$ of order 10 for a range of operating scenarios and with a duration sufficient

to achieve stationary conditions on the time scale characteristic of plasma processes; here, P_{fus} is the fusion power and P_{in} is the input heating power; (2) to demonstrate steady-state operation using non-inductive current drive with at least $Q \sim 5$. In addition, by operating at a higher current (17MA) very high $Q(\sim 50)$ and ignition would be possible. The technological goals of the ITER-FEAT device include the demonstration of integrated operation of technologies essential for a fusion reactor, the testing of components for a future reactor, and the testing of concepts for a tritium-breeding module.

The goals of the IGNITOR experiment² are (1) to demonstrate ignition in a magnetically confined plasma; (2) to study the physics of the ignition process and alpha particle confinement; (3) to heat and control a burning plasma under non-stationary conditions. According to the proponents, a high field, compact approach is likely to provide the cheapest and most expeditious path toward a first burning plasma physics experiment. In addition, IGNITOR may indicate a possible path towards tritium-poor, neutron-poor fusion.

In IGNITOR parameters, a peaked profile with $n_{e0}/n_e = 1.9$ is required to get $Q \sim 10$ ($Q^* = \infty$), as will be discussed in Secs. II.6B and IV. Ignition would be reached under non-steady-state conditions. However, the ignited regime would last a few (5 to 10) confinement times and many alpha particle slowing down

times, which is adequate from the physics point of view but is not long enough to study the helium accumulation and pumping.

The concept of ignition adopted³ by the IGNITOR proponents corresponds to the plasma state where the heating power due to the fusion alpha particles compensates for all forms of power losses (due to anomalous transport and radiation). It is worthwhile to discuss this concept quantitatively, especially in view of non-steady-state operation. Consider the power balance equation,

$$dW/dt = P_{\text{ohm}} + P_{\alpha} + P_{\text{aux}} - P_{\text{loss}},$$

where W is the plasma energy content, P_{ohm} is the ohmic power, P_{α} is the alpha particle heating power, P_{aux} is the auxiliary heating power, and P_{loss} is the loss power, including radiation losses. In the ignited state, $P_{\alpha} = P_{\text{loss}}$ and the auxiliary power, P_{aux} , may be switched off. Thus, ignition would correspond to an overheated state with $dW/dt = P_{\text{ohm}} > 0$. One may introduce a parameter, $Q^* = P_{\text{fus}} / (P_{\text{loss}} - P_{\alpha})$, where the fusion power is given as $P_{\text{fus}} = 5P_{\alpha}$ for a D-T reacting plasma. With this definition, $Q^* = \infty$ at ignition. Alternatively, using the power balance relation, one may write

$$Q^* = P_{\text{fus}} / (P_{\text{in}} - dW/dt),$$

where $P_{\text{in}} = P_{\text{ohm}} + P_{\text{aux}}$.

The parameter Q^* is the one used by the IGNITOR proponents to quantify the proximity to an ignited state. One can see that Q^* becomes equal to the usual $Q = P_{\text{fus}}/P_{\text{in}}$ when $dW/dt=0$, i.e. Q^* is the natural extension of the thermonuclear gain parameter under non-steady-state operation. During transient regimes, the difference between Q and Q^* becomes important and should be kept in mind. For instance, for the simulation example in Table I of an ignited discharge in IGNITOR, one finds $Q^*=\infty$, while $Q=8.6$.

The panel members believe that a value of Q close to ten, sustained for a duration of at least a few confinement times, is the minimum value required in order to study a burning plasma where alpha particle heating is the dominant form of heating. Indeed, $Q=10$ implies $P_{\alpha}=2(P_{\text{ohm}}+P_{\text{aux}})$. We note that both ITER-FEAT and IGNITOR satisfy this criterion, although only marginally.

From the scaling of confinement in tokamaks one can obtain an approximate scaling of Q in terms of major radius and toroidal field in the following manner: $Q \propto nT\tau_E \equiv \beta B(B\tau_E)$. For a gyro-Bohm transport model, $B\tau_E \propto \rho^{*-3} f(v^*, q, \beta)$. Expressing ρ^* in terms of v^* , β , q , R and B we obtain

$$Q \propto B^3 R^{5/2} g(v^*, q, \beta, \kappa) . \quad (1)$$

For gyro-Bohm type of scaling expression similar to IPB98y, g is found to be a very weak function of β and v^* varying as $v^{*1/2}$. From the above equation, we can see that there is a complete family of tokamaks with different values of B and R , that can in principle give the same Q . IGNITOR with $B = 13\text{T}$ and $R = 1.32\text{m}$ is at one end of the range and ITER-FEAT with $B = 5.3\text{T}$ and $R = 6.2\text{m}$ is at the other end.

There have been several other proposals with intermediate values of R and B , for example FIRE: $B = 10\text{T}$, $R = 2\text{m}$; BPX: $B = 9\text{T}$, $R = 2.6\text{m}$; LHT: $B = 8\text{T}$, $R = 3.4$; MT2: $B = 5.4\text{T}$, $R = 5\text{m}$. The cost of each of these machines increases approximately with the major radius, but also the range of physics phenomena that can be addressed also increases with the size. For example, the length of the burn in terms of the number of helium confinement times increases from $\tau_{burn} \sim \tau_{He}^*$ in Ignitor to $\tau_{burn} \sim 25\tau_{He}^*$ in ITER-FEAT.

Table II compares the main physical parameters of JET, IGNITOR, and ITER-FEAT, including the three dimensionless parameters, ρ_* , β_N and v_* . This table shows that the three tokamak plasmas have values of ρ_* , within a factor of two of one another. The value of β_N is lowest for IGNITOR, which is an asset from the point of view of improved MHD stability. The

value of the collisionality parameter, ν_* , is a factor of 10 higher in IGNITOR than in ITER-FEAT; the present L and H mode data encompass this range. One other interesting feature of Table II is the close proximity of IGNITOR in its dimensionless parameters to JET D-T L-mode pulses; this is due to low β operation of IGNITOR. This means that these JET L-mode plasmas potentially form a useful test bed for IGNITOR modeling studies.

During the discussions in Paris, problem areas emerged for both the proposed IGNITOR and ITER-FEAT devices. The question was how to deal with these problems in an effective manner. For a fair and productive scientific assessment, it was considered to be important that the same guidelines be applied to all experimental proposals. The terms of references were stated by Rene Pellat as follows:

“The assessment will deal in particular with:

- The physics basis for each device and the confidence in achieving the performance required for reaching the stated objectives. In particular, confinement, stability, power, and particle extraction, and D/T burning (with the possibility to reach ignition) will be examined.

- The contribution of each facility to the above reactor-oriented strategy: enrichment of experimental databases

with respect to thermonuclear physics and control of burning plasmas; extrapolation of the expected results to reactor conditions."

These terms of reference will be taken as a basis for the report. Consequently, technical aspects of the projects, engineering feasibility and reliability of the proposed devices will not be assessed. Costs and construction opportunities should not be mentioned in this report.

Table I: Nominal parameters of ITER-FEAT and IGNITOR as given by the proponents, see Ref. [1] and the February 2000 revised version of Ref. [2].

Parameter	ITER-	IGNITO
R/A (m/m)	6.2/2.0	1.32/0.47
B_T (T)	5.3	13
I_p (T)	15.0	11
κ_x/δ_x	1.84/0.5	1.83/0.4
q_{95}	3	3.5
β_p	0.65	0.26
$\beta_T\%$	2.6	1.2
β_n	1.81	0.67
$\langle n_e \rangle, n_e$ ($10^{20}/\text{m}^3$)	1.0, 1.0	5.0, 6.2
$n_e(0)$ ($10^{20}/\text{m}^3$)	1.1	9.5
n_e/n_{GW}	0.85	0.4
$T_e(0)$ (keV)	23	11.5
$T_i(0)$ (keV)	19	10.5
P_{OH} (MW)	1	11
P_{ICRH} (MW)	7	0 ¹

JET D-T L- mode	3.9	3.7	0.94	3.9	2.9	3.6	1.4	2.9	1.8	0.4	2.1
IGNITOR at ignition	13.0	11	0.47	62	13	13	4.2	3.0	1.7	0.7	4.0
ITER- FEAT	5.3	16	2.0	9.7	470	22	9.0	2.3	1.4	1.6	0.4

Notes:

1. We have used the following definitions: $\rho^* = 5.1 \cdot 10^{-3} T_i^{1/2}/Ba$
and $\beta_N = 8.5W/a \kappa RBI$.
2. Of the several definitions of $\langle v_* \rangle$, we follow K. Lackner,
Physical Equivalence of Tokamak Discharges, *Comments Plasma
Phys. Control. Fusion*, 1990, **13**(4), 164.
$$\langle v_* \rangle = R/\lambda_{mfp} = 7.5 \times 10^{-6} a^7 n^3 \kappa^2 Z_{eff}/\epsilon^{3/2} W^2$$

II. IGNITOR PHYSICS ASSESSMENT

1. Goals of the IGNITOR experiment

IGNITOR^{2,4} is a physics demonstration experiment. Its main goal is to achieve thermonuclear ignition, defined as the regime where the fusion alpha heating compensates for the thermal energy losses due to anomalous transport and radiation. The relevant information that would be gained from such an experiment can be summarized as follows:

(i) Improved understanding of plasma turbulence and transport processes, by the exploration of high-plasma-density, high-magnetic-field regimes never accessed before. More specifically, IGNITOR would provide insight into the ohmic confinement scaling laws and self-organized plasma profiles at high temperatures. Furthermore, it would provide relevant information on the conditions required for the spontaneous generation of plasma rotation through anomalous angular momentum transport. Plasma rotation is believed to play an important role in determining the level of turbulent fluctuations.

(ii) Alpha particle physics issues, in particular: alpha particle confinement, collective electromagnetic modes excited by the fusion alphas, and the nature of alpha particle heating. We note that an outstanding alpha physics issue is whether collective instabilities excited by the fusion alpha particles, such as fishbones and Toroidal Alfvén Eigenmodes (TAE), can seriously degrade the quality of confinement. A second outstanding physics issue is whether alpha particle heating causes the same degree of confinement degradation as other forms of auxiliary plasma heating.

(iii) The control of a fusion burning plasma over physically significant time scales. With a current flat top of a few seconds, IGNITOR should have a long enough pulse-length to thoroughly

examine alpha particle physics and thermal transients associated with the DT burn.

(iv) The IGNITOR experiment would give first indications about a possible development path to tritium-poor, reduced neutron production of fusion power.

While IGNITOR would represent a long-awaited fusion ignition demonstration and a possible way to study some burning plasma issues at relatively low cost, it is noted that reactor-relevant technological issues are not a motivating factor. It is noted, however, that some of the technological solutions found by the IGNITOR team, such as the so-called bucking and wedging structural concept for the magnet coils system, have also been adopted by the ITER design.

2. IGNITOR operational flexibility

Tokamak plasmas are complex physical systems⁵. As such, it is generally accepted that our confidence in accurate quantitative predictions of plasma behaviour in future tokamak experiments is relatively limited. Experiments such as IGNITOR are precisely designed having in mind the exploration of new plasma regimes and unforeseen plasma behaviour. In this respect, any new tokamak experiment must have sufficient flexibility in order to counter unexpected plasma behaviour. The flexibility of the IGNITOR experiment is related to:

(i) Its ability to explore a wide range of plasma densities and currents;

(ii) The operation of a high-speed pellet injector for the control of plasma profiles and for the exploration of enhanced confinement regimes.

(iii) The presence of a 18-24 MW Ion Cyclotron Radio Frequency system capable of providing additional heating, thereby affecting the current density evolution, and also capable of producing a suprathermal minority ion population for the control of MHD instability and for the simulation of alpha particle behaviour. For instance, ICRH can be applied to relatively low-density regimes, in which the plasma temperature can be raised to values considerably higher than the optimal values for ignition, to attain the desired ratios of fast particle pressure relative to the plasma pressure.

(iv) A highly flexible poloidal field coil system, able to produce a considerable variety of equilibrium configurations. This includes the possibility of producing magnetic X-point configurations as an added tool for the investigation of enhanced confinement regimes.

3. A short assessment of plasma performance in present high-field tokamak experiments

IGNITOR belongs to a family of high-field tokamak experiments, pioneered by the Alcator machine at MIT in the 1970s and continued by the Alcator C/C-Mod and the Frascati FT/FTU series of experiments. A full assessment of plasma performance in these experiments is beyond the scope of the present work. It is noted, nevertheless, that a record value of $n_0 \tau_E \sim 1 \times 10^{20} \text{ m}^{-3} \text{ s}$ was reached in ALCATOR C experiments^{6,7} with high peak density ($n_0 \sim 2 \times 10^{21} \text{ m}^{-3}$) and a confinement time of about 0.05s. In IGNITOR, a value of τ_E higher by about a factor of ten is needed to reach the target value $n_0 \tau_E \sim 6 \times 10^{20} \text{ m}^{-3} \text{ s}$.

Experience from ALCATOR C-MOD⁸ and from FTU⁹ indicates that the worst-case discharges in these machines have a confinement time that follows the ITER89P L-mode scaling, both in ohmic and in auxiliary heated discharges at relatively high densities, while the neo-Alcator scaling is followed at lower densities. Regimes of improved confinement at high plasma density have been observed. H-modes have been observed in limiter as well as divertor configurations, in ohmic as well as in auxiliary heated discharges. Enhanced confinement in L-mode

type of operation, such as the Improved Ohmic Confinement (IOC) regime of the type observed in ASDEX-U,¹⁰ has been observed in Alcator C at relatively high density in plasmas with peaked density profiles.

We note, however, that high-field operation in recent experiments has been limited. As a result, the available data bank is rather poor. It would be desirable to extend the database to more Ignitor-relevant demonstration discharges in order to increase the margin of confidence for extrapolations to Ignitor.

4. MHD stability and collective alpha particle modes

One of the main assets of the IGNITOR experiment is the increased safety margin against MHD instabilities. The relatively low values of the plasma beta parameter and relatively large values of the safety factor needed at ignition guarantee this. Thus, IGNITOR should operate well below the stability thresholds for ballooning modes and for longer time scale neoclassical tearing modes. Likewise, the incidence of disruptions in IGNITOR can be expected to be very low. However, a more precise quantitative assessment of MHD stability requires further work.

The assessment of stability against internal kink modes, leading to the well-known sawtooth internal relaxation oscillations and fishbone oscillations, deserves a separate discussion. Here, the IGNITOR team has carried out a

considerable amount of in depth work^{2,4}. Indeed, it appears as if the ignition strategy in IGNITOR is partly driven by the necessity to avoid the deleterious effects of sawteeth. The transient nature of the approach to ignition is such that the q profile may develop a $q=1$ surface only well into the current flat top, after ignition is reached. In this way, the $q=1$ radius, which measures the extent of the central plasma region affected by sawteeth, should remain small. Thus, if sawteeth appear at all, their effect should cause only a minor redistribution of the plasma core properties. However, anomalous current penetration, for instance caused by double tearing modes, may lead to an early onset of sawtooth oscillations. In addition, a detailed analysis of the evolution of the current density profile and of the sawtooth trigger condition in the presence of alpha particles and of kinetic effects related to trapped thermal ions has not been carried out.

Fishbone oscillations may be excited by the fusion alpha particles in IGNITOR. The relevant instability regime corresponds to modes oscillating at the thermal ion diamagnetic frequency.¹¹ Trapped alpha particles can resonate with these modes only at energies below 500 keV, i.e., only after they have deposited most of their energy in the plasma. The effect of fishbones on slowed-down alphas at these relatively low energies should be relatively mild. It is noted that the loss of slowed-

down alpha particles may even be beneficial, as the deleterious effect of alpha ash accumulation would be reduced.¹²

Since IGNITOR is designed to reach ignition at relatively low plasma temperatures, the projected alpha particle pressure is relatively low, in particular lower than the threshold for the excitation of Toroidal Alfvén Eigenmodes (TAE). However, operation at lower density and ICRH injection lead to higher plasma temperatures and higher alpha particle pressures, which could then allow for the experimental observation of TAE modes.

IGNITOR is expected to operate at such low poloidal beta that neoclassical tearing modes would only be very weakly excited, if at all. Also, even if they did occur they would probably grow too slowly to influence the approach to ignition. To the extent that a burning plasma regime is achieved and sustained for a time of the order of the skin diffusion time in IGNITOR, neoclassical tearing modes might be observed and studied. However, at the high collisionality in IGNITOR, the threshold island width is likely to be quite high. Thus, neoclassical tearing modes seems to be of little concern for IGNITOR's basic mission.

5. Impurities

Another important asset of the IGNITOR experiment is the expected high purity associated with high plasma density operation. The self-cleaning ability of high-density plasmas has been well documented by Alcator C-MOD⁸ and FTU¹³ experiments. A scaling law relating plasma purity, radiated power, and machine dimensions has been derived from a number of experiments.¹⁴ Based on these experiments, average Z_{eff} values of around 1.2 should be possible in IGNITOR. However, the problem of plasma purity is associated with the problem of reducing the power load on the first wall, where sputtering and evaporation can produce impurities.

One possible solution to this problem is the divertor concept. However, while the IGNITOR poloidal system may be capable of producing an X-point within the vacuum vessel, the IGNITOR first wall is not capable of handling the concentrated power load associated with divertor operation. Hence, this solution appears impractical for IGNITOR.

The solution proposed by the IGNITOR team is the *cold radiating mantle* concept, with molybdenum tiles as the first wall material. In the high-density regimes at which IGNITOR is expected to operate, strong screening of the main body of the plasma column from impurities has been observed. Recent experimental results¹⁵ have indicated the possibility of operating

with a radiating mantle able to dissipate up to 90% of the total power lost by the plasma without energy confinement degradation. Thermal loads in IGNITOR have been calculated for an ideal continuous first wall, under the conservative assumption that only 70% of the input power is radiated. Under normal operation, the maximum thermal load is estimated⁴ to be 1.8 MW/m^2 with an average heat flux of less than 0.7 MW/m^2 .

6. Transport considerations

The study of plasma transport is one of the outstanding problems in fusion research. Following Kadomtsev⁵:

At the beginning of tokamak research there was the hope that experiments would allow us to determine empirical expressions for the relevant transport coefficients, which would then be explained theoretically. This hope was supported for a decade by results from small and medium size tokamaks, which suggested that the ion thermal conductivity was close to the neoclassical value. As for electrons, there was hope that experiments might help to produce a universal formula applicable to all cases. Understanding of confinement deepened in the 80s partially as a result of more detailed investigations in medium-size tokamaks,

but mainly as the result of the operation of the new generation of large size tokamaks, such as JET, TFTR, JT60. A new understanding has emerged as a result of the discovery of various confinement regimes.

It has become evident that self-consistent coupling of the turbulence with the plasma profiles plays a crucial role in the determination of the effective transport coefficients. Due to the feedback loops within this complex dynamical system, bifurcations arise analogous to those well known in turbulent neutral fluids. Thus, there are a variety of plasma confinement states. In some cases, similar system control parameters result in discharges that take different confinement paths. A well-known example occurred for the matched discharges in TFTR, in which one ultimately deviates from the other through the bifurcation to a new state known as Enhanced Reversed Shear (ERS) confinement¹⁶. These issues of plasma confinement are of fundamental importance to plasma science and can be addressed in fusion-grade plasmas with IGNITOR.

The IGNITOR team bases its confinement predictions on a combination of empirical and theoretical 1-D flux-surface-averaged transport models.⁴ While such 1-D models are intellectually appealing, the unfortunate reality of tokamak

physics is that we do not have a generally accepted model of turbulent transport.

The confinement issue for IGNITOR should be addressed with various methodologies and from many different perspectives in order to make sure that the confinement will be sufficient for the ignition objective. One methodology is to examine the heat diffusivity value needed for ignition in IGNITOR relative to what has been achieved in other high field, compact tokamak experiments. Table IV provides one possible comparison:

Table IV: Comparison of Alcator C and C-Mod with IGNITOR

Plasma parameters

	Alcator C(1983)	Alcator C- Mod (1996)	IGNITOR
$a(m)$	0.165	0.22	0.47
$R_0(m)$	0.64	0.67	1.32
κ	1	1.65	1.83
B(T)	11.2	5.4	13
I(MA)	0.78	1	11

Plasma confinement performance

	Alcator C(1983)		Alcator C Mod(1996)		IGNITOR
	Normal density profile	Peaked density profile	L-mode	H-mode	PTP99/06 p. 33
$\tau_E(s)$		0.05	0.04	0.08	0.5
$\chi_E(m^2/s)$	0.025 0.27	0.136	0.5	0.25	0.2

In Table IV, as suggested on p. 33 of the February 2000 version of Ref. [2], the definition $\chi_E = a^2 \kappa/4 \tau_E$ has been used.

Table IV shows that an average heat diffusivity as low as that needed for ignition in IGNITOR has been achieved - viz., in Alcator C in 1983, with the use of pellet injection to produce a peaked density profile, enhanced confinement regime plasma. However, normal density profile plasmas in Alcator C and a large number of later tokamak experiments throughout the world have apparently not been able to produce a low enough diffusivity for ignition in IGNITOR.

It is not clear how to extrapolate these lower temperature ($T_I \sim 1.5$ keV in Alcator C and 3 keV in C-Mod) plasmas to the proposed Ignitor regime plasmas ($T_I \geq 10.5$ keV). However, both Bohm and gyroBohm scalings mostly indicate increases in

the extrapolated values of average heat diffusivities that could be anticipated in IGNITOR. The one exception is that for the gyroBohm extrapolation from C-Mod to IGNITOR the factor is 0.53 to 0.57 (with mass and elongation effects), which yields χ_E values similar to those in Alcator C, whereas the same extrapolation from Alcator C to C-Mod is off from the experimental results in C-mod by a factor of 5.

A significant concern as one moves to the larger, higher temperature plasmas required for ignition is that of fueling. Early tokamak plasmas were mostly gas fueled from the edge by means of edge Frank-Condon and charge-exchange neutral sources, which yielded moderately peaked density profiles. However, as the plasma minor radius has increased over the past two decades, this fueling source has become more localized to the very edge ($\leq 3\%$ of the minor radius) of the plasma, the density profiles have become flatter, and the rate of core plasma density build-up has slowed considerably. On the other hand, almost all enhanced plasma confinement regimes have highly peaked density profiles and seem to require significant core sources of power and particles to build up the peaked profiles on the confinement time scale. In most present-day auxiliary heated plasmas, the peaked density profiles are produced by the core fueling provided by energetic neutral beams. A very peaked

density profile and enhanced (mainly in the ions) confinement was produced in Alcator C by pellet fueling. However, hydrogenic ice pellets have difficulty penetrating plasmas with temperatures above 2 keV unless their velocity is increased rather substantially. Inside launch pellets seem to penetrate better into medium density plasmas, but they have not yet been tried on high density plasmas.

Our preliminary assessment of confinement predictions in IGNITOR is based, in the first instance, on 0-D empirical confinement scaling laws. In particular, we consider a first estimate of confinement time in IGNITOR based on the L-mode scaling law. This estimate should represent the expected lower bound on performance if no care is taken to control the plasma profiles. Then, we consider the possibility of enhanced confinement regimes in IGNITOR. Finally, we present considerations based on the dimensional analysis of energy confinement.

One peculiar feature of the IGNITOR experiment is its transient approach to fusion, which implies that relevant plasma parameters, in particular the ohmic and alpha particle heating powers, vary in time; consequently the confinement time should also be changing in time during the discharge duration.

A. Confinement time based on L-mode scaling laws

A good description of the L-mode database with approximately 3000 entries is given by the ITER97 L-mode formula¹⁷:

$$\tau_E^{L97} = 0.023 \kappa^{0.64} R^{1.83} A^{0.06} B_T^{0.03} n_e^{0.4} m_{\text{eff}}^{0.2} I_p^{0.96} P_L^{-0.73}$$

where n_e is the line-average density, P_L is the loss power that includes ohmic power, auxiliary injected power, the fusion power deposited by the alpha particles minus the rate of variation of stored energy, dW/dt . At ignition, $dW/dt = P_{OH} + P_{aux}$ and $P_L = P_\alpha$. For the reference case of Table I, $P_L = 19\text{MW}$ at ignition. Taking the remainder of the parameters from Table I, with line-averaged density $n_e = 6.2 \times 10^{20} \text{m}^{-3}$, gives $\tau_{E97L} = 0.47\text{s}$; thus to obtain the required confinement time of $\tau_E = 0.62\text{s}$, an H factor of 1.3 would be required. Similarly if the older L-mode scaling expression ITER89-P scaling is used, then $\tau_{E89L} = 0.39\text{s}$ and an H factor of 1.6 is required.

A key scientific issue that IGNITOR would address is whether the ohmic power at multi-megawatt levels plays the same role as P_{aux} in the confinement scaling laws as assumed in the above estimate of the confinement time. The same kind of question arises for the alpha heating power since this would become the dominant form of heating in IGNITOR.

The ITER L97 scaling formula has been compared with confinement in Tore Supra.¹⁸ The Tore Supra database has 50 discharges with Fast Wave ICRH that deposits its energy into the electrons, $P_{\text{ICRH}}=P_0 \exp(-r/L_p)$, in a highly localised core with $L_p \approx a/5$. Thus, the fast wave ICRH heating is a rough simulation of the alpha power heating to the electrons. In addition, Tore Supra operates routinely in L-mode and exhibits various levels of enhancement over the L97-mode scaling law as a function of density profile peaking. Thus, even though not a high field tokamak, Tore Supra is relevant to IGNITOR considerations. The best discharges have an enhancement factor of $H=1.4$ to 1.7 with respect to the ITER 97-L mode formula, which should be a conservative calculation of τ_E .

In a recent contribution by J. Johner,¹⁹ invited by the panel members, IGNITOR L-mode confinement was analysed on the basis of the zero-dimensional thermal equilibrium code HELIOS. The analysis assumed the ITER-97P(th) scaling law and evaluated the enhancement factor, H_L , needed for ignition (defined as the condition where the alpha power can compensate for all forms of power losses) as a function of the profile peaking factors α_n and α_T , where $n(\rho)=(1-\rho^2)^{\alpha_n}$ and $T(-\rho)=(1-\rho^2)^{\alpha_T}$. The ignition simulation example in the IGNITOR report, Ref. [2] could be reproduced by the HELIOS code by assuming the

values $\alpha_n = 1.8$ and $\alpha_T = 2.4$ an enhancement factor $H_L = 1.4$. For parabolic density and temperature profiles, the enhancement factor becomes $H_L = 1.9$. Clearly, the value of H_L required for ignition is lower for more peaked profiles and higher for less peaked ones. It should be pointed out that, in existing tokamak experiments, profile peaking and enhanced confinement normally come together (see the next section). The question arises as to whether adequate profile peaking can be produced and maintained in IGNITOR for a sufficiently long time.

B. Improved confinement regimes with peaked density profiles

Since the IGNITOR proponents suggest that ignition may be reached with ohmic heating only, it is convenient to start our discussion with the consideration of ohmic confinement modes. As is well known, the LOC (linear ohmic confinement) mode is a regime of ohmic confinement where a linear relationship between energy confinement time and density, i.e. neo-ALCATOR scaling, is valid.²⁰ The LOC regime corresponds to the best confinement mode. Unfortunately, at regular conditions with increasing density, the LOC regime makes a transition either into a saturated ohmic confinement (SOC) mode or into the L-mode with Goldston confinement scaling. The critical

density at which the transition between LOC and SOC regimes occurs is the so-called Shimomura density²¹, whose expression is

$$n_s \approx (A_i/2)^{1/2} B_T / q_\psi R ,$$

where n_s is the density in $10^{20} m^{-3}$, A_i is the atomic mass number, B_T is the toroidal field in Tesla and R is the major radius in meters.

Different improved confinement regimes look like a LOC mode extended into the high-density region with subsequent saturation. One such improved confinement mode, the H-mode, will be discussed in Subsec. 6D. Here, we consider improved confinement regimes that can be reached with peaked density profiles. These regimes are listed as follows:

(i) The improved ohmic confinement (IOC) mode, initially discovered in ASDEX.¹⁰

(ii) The radiative improved (RI) mode, discovered in TEXTOR.¹⁵

(iii) The P-mode, which is a mode of improved ohmic confinement both in ohmic and in auxiliary heated discharges, first obtained with the help of pellet injection in ALCATOR-C.⁶

(iv) The supershot, or S-mode, experimentally discovered in TFTR with central neutral beam injection (NBI) and strongly peaked density distributions.²²

(v) Fast Wave ICRH on Tore Supra.¹⁸

In the experimental regimes listed above, energy confinement enhancement factors up to 2-3 over that for L-mode have been obtained. Clearly, the relevant question is whether IGNITOR can access any of these regimes. Note that the key feature common to these improved confinement regimes is the realisation of peaked density profiles. Different methods and considerable operational skills in the four tokamaks mentioned above have achieved this. In ASDEX, peaked densities and the IOC mode were obtained after appropriate wall conditioning and decreased gas puffing. In TEXTOR, the transition from the L to the RI mode was obtained with impurity seeding. In this way, a strongly radiating layer was established at the edge, with a corresponding decrease of the edge temperature and a steepening of the density gradient deeper inside the plasma. In ALCATOR-C, pellet deposition in the plasma core resulted in peaked density profiles and the establishment of the P-mode. In TFTR, very peaked densities were obtained in supershots with central NBI deposition.

From a theoretical viewpoint, peaked density profiles are known to have a beneficial effect on plasma confinement through the quenching of the ion temperature gradient (ITG) driven turbulence. Peaked density profiles reduce the two dimensionless profile parameters, η_i and η_e , that represent driving terms for the instability of ion and electron temperature gradient modes and

their associated plasma turbulence for peaked density profiles. For flatter density profiles, the ITG stability condition is that L_{Ti}/R exceed a critical value, which is typically not compatible with the overall required temperature difference between the edge and core plasmas. In the 80s, several theoretical investigations of ITG modes supported the conclusion that the improved confinement in Alcator C pellet fueling experiments⁶ was correlated in time with the drop of the η_i parameter. Numerous other machines have shown discharges with improved confinement from density peaking. For instance, Ref. [23] predicts suppression of the ion thermal flux due to ITG turbulence going from L-mode to the RI-mode in TEXTOR.²⁴ As far as the electron temperature gradient driven turbulence is concerned, there are two theoretical forms of the anomalous electron thermal diffusivity that are depressed by high density: the dissipative trapped electron turbulent diffusivity, and the short wavelength electromagnetic diffusivity with mixing length proportional to the collisionless skin depth.²⁵

In IGNITOR, ignition would be reached with densities well below the Greenwald density limit, which must be considered as a distinct advantage. However, density peaking is crucial to gain access to improved confinement regimes. Strong density peaking in IGNITOR depends on the existence of an inward particle pinch. There are two theoretical models used to explain the

particle pinch that occurs in tokamaks. The classical mechanism known as the Ware pinch is the off-diagonal transport coefficient that is conjugate through symmetries to the experimentally verified bootstrap current. While no clear experimental verification exists for the Ware pinch, an inward convection is required for transport modeling to be consistent with the measured density profiles. The density pinch effect is also modeled through drift wave turbulence driven by the temperature gradients, where again symmetries dictate an off-diagonal transport matrix producing a turbulent inward particle transport.²⁶

As noted in Sec. 5, IGNITOR has adopted the cold radiating mantle solution, which may turn out to be advantageous for the formation of peaked density profiles. Indeed, the qualifier *radiative* in the RI-mode refers to the fact that this mode was discovered in TEXTOR while the cold plasma mantle concept was being established as a feasible means to solve the reactor exhaust problem.²⁷ Modeling the density profile with the RITM code has shown²⁷ that an essential ingredient for peaking of the density profile is the action of the radiative mantle on the anomalous inward pinch velocity v_{in} , which is taken to have the form $v_{in} = 1/(2T_e)(dT_e/dr)D$, where D is the perpendicular particle diffusivity. This form may be justified by arguments of profile consistency, but more generally as a fundamental off-diagonal contribution of the transport matrix for fluctuation-driven particle

transport.²⁸ It was also found to be essential in explaining the SOC-IOC transition in ASDEX.²⁹

The question of the degree of profile control by high-speed pellet injection, which translates into the question of the penetration of the pellet particles in high-density plasmas, thus becomes a crucial issue for the IGNITOR project. Possible solutions for how to inject pellets from the high field side and facilitate pellet penetration must be investigated. Control of the plasma edge density during start-up and current flat top is also important, since it regulates the current penetration rate, as well as being related to the edge temperature.

C. Reversed magnetic shear modes

In the IGNITOR device, transient effects can be exploited to reach ignition in ohmically heated plasmas. When the current ramp is considered, the plasma current increases by adding skin layers on the outer surface of the plasma column. The current penetration time based on neoclassical resistivity is comparable to the pulse length time scale. As a consequence, non-monotonic q profiles may form during the current ramp and during a significant fraction of the current flat top. Since ignition is expected to be achieved near the end of the current ramp, IGNITOR is well suited for a Reversed Shear (RS) mode of operation¹⁶ of the type observed in JET and in TFTR, among

other devices. The PEP mode,³⁰ which is the JET variant of the RS mode, was obtained with central ICRH and pellet injection. For these modes of operation, enhancement factors of $H \cong 2-3$ can be achieved. The physics of confinement enhancement for a non-monotonic q profile clearly has basic differences with that in a monotonic q profile. It is possible that reversed magnetic shear is only one factor in achieving reduced turbulence, with sheared plasma rotation and/or peaked profiles also playing important roles. Thus, although non-monotonic q profiles may occur spontaneously in IGNITOR, the assistance of pellet injection and ICRH in accessing enhanced RS regimes of operation seems rather important.

D. H-modes

H modes of operation normally require the presence of a magnetic X-point and heating power levels above a threshold value. The L-H power threshold formula recommended by the ITER physics expert group is

$$P_{\text{LH}}^{\text{IPB99(5)}} = 3.24 n_e^{0.62} B^{0.75} R^{0.98} a^{0.81} m_{\text{eff}}^{-1} .$$

If an H mode is accessed, the ITER ELMy H-mode scaling law predicts a confinement time according to the formula

$$\tau_E^{\text{IPB98}} = 0.0562 k^{0.78} R^{1.97} A^{-0.58} I_p^{0.93} B_T^{0.15} n_e^{0.41} m_{\text{eff}}^{0.19} P^{0.69} .$$

For IGNITOR, these formulae give a power threshold

$P_{\text{LH}}^{\text{IPB98}}$ (IGNITOR) ≈ 17 MW, easily exceeded by a combination of ohmic and ICRH or alpha heating, and a confinement time at ignition of $\tau_E^{\text{IPB98}} \approx 0.78s$. Again the parameters of the example simulation in Table I have been used in these estimates. With these values of the confinement time, there should be no problem to reach ignition in IGNITOR. Similar conclusions were reached by Johner.¹⁹

It is noted that the IGNITOR poloidal field system is capable of producing an X-point within the vacuum vessel, in which case IGNITOR has sufficient power for a transition to H-mode confinement. However, the IGNITOR first wall may not be capable of handling the localised heat fluxes associated with divertor operation. Thus, standard H-mode operation is not desirable in IGNITOR. On the other hand, H-mode quality plasmas have sometimes been obtained with the magnetic X-point outside the vacuum vessel. Indeed, H-modes have been observed in limiter configurations.³¹ Furthermore, there is evidence from Alcator C-MOD of an enhanced L-mode with the magnetic X-point inside the vacuum vessel.³² In this case, the plasma is prevented from entering the H-mode by reversing the toroidal magnetic field so to set the ∇B drift away from the single null divertor. For power thresholds well in excess of those that would be required for an L-H transition (if the ∇B drift

were in the favourable direction), enhancement factors of 1.2-1.4 relative to L-mode have been obtained.

In all these cases, a more favourable, i.e. more uniform, heat flux distribution to the first wall may result. Thus, improved confinement assisted by X-point operation is a possibility worth exploring in IGNITOR, although at present the available experimental information is insufficient to be able to rely on this.

7. Burn control

Development of burn control techniques is one of the major areas of investigation for IGNITOR. Transport simulations indicate that precise time-dependent burn control through variation of the plasma density is difficult if the particle confinement time is longer than the energy confinement time, as would be expected for IGNITOR. Much better control is possible by operating in a slightly sub-ignited state driven by a small amount of ICRH heating. This may be the preferred mode of operation for a reactor and would constitute an important physics demonstration on the path to a reactor that could be carried out in an ignition experiment.

Emergency methods of burn control include the firing of a *killer pellet* into the plasma to rapidly quench run-away ignition conditions and prevent or mitigate a possible disruption. This method has been adopted in IGNITOR.

Fusion reactions with low rates of neutron production, utilising advanced fuels such as D-³He or possibly D-D, may be more attractive than the D-T reaction, which produces 80% of its energy in 14 MeV neutrons. To begin exploring fusion with advanced fuels, a D-T burning plasma experiment at high field is much closer to the required parameters than present-day large size tokamaks. IGNITOR would allow initial studies at the level of approximately 1 MW of power in charged particles from the D-³He reaction cycle.

8. Conclusions

IGNITOR is essentially an ignition physics experiment, which is projected to bring a long-awaited demonstration of the scientific feasibility of magnetic fusion and a possible way to study alpha particle and burning plasma issues. The main assets of IGNITOR are its high magnetic field and low beta, which increase safety margins with respect to MHD instabilities, and its expected high purity plasma. With high ohmic heating and intense ICRH, it should be possible to access interesting regimes without relying on alpha particles and a highly irradiated environment. Thus, the physics exploration of confinement regimes and optimisation could go far before the difficult ignition runs.

Any tokamak experiment in unexplored plasma domains should possess sufficient versatility to counter unexpected adverse behaviour and to explore a wide range of operational scenarios. IGNITOR flexibility lies in its ability to produce a wide range of plasma densities and currents and a variety of equilibrium configurations, including the capability of producing a magnetic X-point. The key to IGNITOR success, however, relies on adequate density profile control with the assistance of a high-speed pellet injector and adequate power injection from an ICRH system, capable of sustaining the plasma temperature at relevant values should ohmic scenarios fall short due to poorer than expected confinement properties. Pellets and ICRH would also allow relevant burn control studies at slightly sub-ignited states.

Ignition in limiter discharges is a distinct possibility in IGNITOR. However, this relies importantly on accessing improved confinement regimes with an enhancement factor of about 1.3-1.6 over predictions of confinement time based on L-mode scaling laws. Improved confinement regimes, such as the IOC, RI, P and S confinement modes, may be accessed in IGNITOR, provided that peaked density profiles are produced. Again, pellet injection is expected to play an important role in this. Reversed Shear and PEP modes may also be realized, since non-monotonic q profiles may form during the transient approach

to ignition. The control of current penetration, by means of appropriately ramping the current, density and plasma volume, is also crucial in order to optimize ohmic heating and for sawtooth avoidance. H-modes are not desirable in IGNITOR, given the intolerable levels of localised heat flux to the first wall that would result. However an appropriate use of the magnetic X-point may provide some degree of enhancement in L-mode type of behaviour. It should be remarked, nevertheless, that transport in tokamak plasmas is not fully understood and that predictions about confinement performance should be taken with great caution.

III. ITER-FEAT PHYSICS ASSESSMENT

Goals and present status of the ITER-FEAT experimental proposal

As stated in Sec. I, the goals of the ITER-FEAT (Fusion Energy Advanced Tokamak) experiment are (1) to achieve extensive burn in an inductively driven plasma with a thermonuclear gain parameter $Q = (P_{\text{fus}}/P_{\text{in}})$ of order 10 for a range of operating scenarios and with a duration sufficient to achieve stationary conditions on the time scale characteristic of plasma processes; and (2) to demonstrate steady-state operation using non-inductive current drive with at least $Q \sim 5$.

Ignition would also be possible in ITER-FEAT with either a 10% improvement in the confinement at the reference current of 15MA or by operating at a higher current of 17MA. However, it would require operation closer to density, beta, and confinement limits simultaneously and this introduces uncertainty as regards the performances in such regimes. Consequently, ignition is not considered as the main objective of ITER – FEAT.

The technological goals of the ITER-FEAT device include the demonstration of integrated operation of technologies essential for a fusion reactor, the testing of components for a future reactor, and the testing of concepts for a tritium-breeding module.

The objective of a reactor-scale thermonuclear experiment motivated the governments of the Four Parties - the European Union, Japan, the Russian Federation and the United States - to initiate, in 1987, the International Thermonuclear Experimental Reactor/Conceptual Design Activities (ITER /CDA). This phase, which was completed in 1990, led, in 1992, to the ITER Engineering Design Activities (ITER /EDA) Agreement, aimed at developing an integrated engineering design for a reactor scale tokamak facility that would achieve controlled ignition and extended burn. As envisioned by the Agreement, the ITER device would be the central element of an international, “one step to a reactor” strategy.³³

Because of the way the project was set up, the original ITER proposal (whose Final Design Report is referred to as ITER-FDR³⁴), enjoyed a broad base of participation. From the point of view of clarification of the relevant physics issues, a tremendous experimental and theoretical effort was set in motion, which involved a large fraction of the international scientific community. This effort culminated with the preparation of the ITER Physics Basis document.³⁵ The panel members are satisfied that the ITER physics assessment in this document represents the state of the art for knowledge of plasma physics issues applied to ITER-FDR.

The US partner withdrew from the ITER project in 1998, partly following cost considerations. This has forced the remaining three partners to reconsider the project, mainly to redefine a reduced-cost ITER device, which would be affordable by the three partners alone (Ref.: ITER-FEAT report, presented to the panel). This reduced cost version, ITER-FEAT, has been worked out very recently. The cost of ITER-FEAT is about half of the cost of the original ITER-FDR device (i.e., about 3.3 billion US\$). It is expected that most physics considerations that applied to ITER-FDR, detailed in the ITER Physics Basis Document³⁵ remain valid also for ITER-FEAT. However, some of the panellists expressed uneasiness about the fact that, since the ITER-FEAT proposal has been put on the table only very

recently, not enough time to reconsider the relevant physics issues for ITER-FEAT has been allowed, considering the reduced dimensions and modified objectives of the device. Nevertheless, the general impression was that the recent moves of the ITER-FEAT project to a reduced fusion technology emphasis, and to a sustained burn at $Q = 10$ objective, along with enhanced flexibility for exploiting advanced tokamak modes of operation, are appropriate steps toward reducing the cost and enhancing the scientific viability and flexibility of ITER.

The scientific assessment that follows is limited to the few problem areas for ITER-FEAT that emerged at the Paris meeting, namely: (1) Transport and confinement; (2) Resistive MHD stability; (3) Alpha particle issues; and (4) Thickness of the scrape-off layer.

1. Transport and confinement

The reference scenario for the operation of ITER-FEAT at $Q \sim 10$ is the ELMy H-mode. According to the ITER-IPB98(y,2) scaling law, a confinement time of about 4s is predicted, which together with the expected plasma density and temperature would be appropriate for the attainment of the declared goals with a good margin of confidence.

It is noted, however, that the projected ITER-FEAT plasma would differ from existing plasmas in large size devices in two important aspects:

(i) ITER-FEAT plasmas would operate close to the Greenwald density limit. In present experiments, a deterioration of confinement is sometimes observed, starting from density values about 70% of the Greenwald density.³⁶ This is certainly an issue that has recently received considerable attention and sophisticated fuelling techniques have now been used to obtain densities in excess of the Greenwald density limit with little degradation in confinement.

(ii) ITER-FEAT plasma will have a relatively low toroidal rotation velocity as compared to present experiments, in view of the large size of the plasma. Velocity fields are known to quench turbulent fluctuations and to ameliorate MHD stability, therefore caution is needed when extrapolating from present experimental data to ITER slowly rotating plasmas.

2. Resistive MHD stability of ITER-FEAT

The ITER-FEAT reference scenario corresponds to plasmas operating at about half of the ideal MHD limit. While this appears as a significant margin with respect to ideal MHD macroscopic instabilities, the present understanding is that the actual beta limit is established by resistive MHD modes, which

are driven in part by pressure gradients and neoclassical effects, most notably resistive internal kinks and neoclassical tearing modes, discussed in subsection A and B below.

A. Resistive internal kinks and monster sawtooth oscillations

Sawtooth oscillations are expected to play an important role in ITER-FEAT, not as much because of their direct impact on confinement, but because of possible couplings between sawteeth and other (non-ideal) MHD activity. Indeed, recent experimental evidence from DIII-D³⁷ suggests that sawteeth may induce seed islands for the growth of neoclassical tearing modes.

Furthermore, sawteeth may couple to locked modes and edge perturbations, such as ELMs and external kink.³⁸ These couplings may effectively limit the achievable values of the β parameter in ITER-FEAT. On the other hand, recent ITER demonstration experiments on JET³⁹ and long pulse demonstration plasmas in other tokamaks^{40,41} indicate that sawtooth activity at ITER-FEAT relevant dimensionless parameters is either absent or, if present, does not necessarily hinder the plasma performance. In addition, sawteeth can be controlled by current drive and auxiliary heating methods, which will also be operational in ITER-FEAT.

The sawtooth crash is triggered by the instability of an internal kink mode when the value of the helical winding index

for magnetic field lines, q , drops below unity in the central plasma region. It is worth recalling that the theoretical ideal MHD beta limit, β_{mhd} , assumes optimal profiles for which, in particular, $q \geq 1$ is satisfied everywhere. When q drops below unity, a new class of ideal MHD instabilities is predicted to occur with $\beta < \beta_{\text{mhd}}$, internal kinks being one of them. However, it is clear from experiments that ideal MHD theory is not accurate in predicting the threshold for the onset of the sawtooth crash. For instance,⁴² sawtooth crashes can be suppressed for long periods in discharges where a significant population of high energy ions is present, even when the value of $q_0 \equiv q(0) < 1$ is less than unity and the value of the thermal plasma poloidal beta, β_p , is well in excess of the threshold value for ideal internal kinks.^{43,44}

A quantitative assessment of sawtooth stability in ITER-FDR was presented in Ref. [45]. We expect this analysis to remain essentially valid for the new design, ITER-FEAT. Based on this analysis, we may conclude that sawteeth will not hinder the performance of ITER-FEAT, as far as the approach to a burning plasma regime is considered. However, in the presence of fusion alpha particles, giant, monster-like sawteeth may appear, which may limit the duration of the good performance phase to times of the order of 10-50 s. On the other hand,

feedback stabilisation methods can be used and should be investigated in present experiments.

More specifically: A fully penetrated q profile for a typical ITER-FEAT reference discharge has its $q = 1$ radius at about half the plasma minor radius. This profile is likely to be unstable to internal kink modes. The situation, however, is not dissimilar from that of the ITER demonstration discharges mentioned above. In non-ignited ITER discharges, the sawtooth period is predicted to be about 1s, i.e., a fraction of the expected confinement time, and the sawtooth amplitude is small [45]. The likely consequence of small amplitude, frequent sawtooth activity is to prevent full penetration of the current, i.e., to keep q on axis close to unity (perhaps $q_0 \approx 0.8$), and to keep the pressure profile relatively flat from the axis up to the sawtooth mixing radius. The ITER team has already allowed for this in transport simulations [35], with the finding that this situation does not degrade significantly the energy confinement time.

Of more concern would be monster-like sawtooth crashes, which could couple to edge activity (external kinks, ELMs etc.), causing a significant degradation of plasma confinement. Monster sawteeth may arise in ignited ITER-FEAT discharges due to the presence of energetic alpha particles, which would play a role similar to that of fast minority ions produced by ICRH in JET. Fast ions are believed to be the cause of monster

sawteeth in that machine. In this respect, several considerations can be made.

The period of monster sawteeth in ITER-FEAT is predicted to be on the order of (10-50 s). This figure is an extrapolation from JET, where the monster sawtooth period is a few seconds long, given that the ratio of the resistive diffusion times for the two machines is of order 10. Thus, the period between monster crashes in ITER-FEAT is several confinement times, which should allow reaching ignition between monster sawtooth crashes, or maintaining ignition for a relatively long time before the onset of the first monster crash. For instance, if the discharge duration were limited to 50 s, the adverse consequences of monster crashes could be avoided.

Heating and current drive scenarios were proposed for ITER-FDR, such that the onset of the first (monster) sawtooth crash is delayed by *several* hundred seconds⁴⁵. This exploited the fact that the projected global current diffusion time in ITER-FDR was exceedingly long, of the order of 10^4 s, so that ignition could be reached well before the current were fully penetrated. Similar scenarios should be applicable to ITER-FEAT as well, although quantitative simulations to ascertain this for realistic power levels should be performed.

Heating and current drive schemes can also be used to *induce* frequent, small amplitude sawteeth, thereby avoiding the

adverse effect of monster crashes. One possible scheme was demonstrated in JET with fast wave current drive. It is essential that dedicated experimental time be allotted in JET and other large-size devices to demonstrate the possibility of monster sawteeth at ITER-FEAT relevant values of resistive MHD dimensionless parameters.

B. Neoclassical tearing modes

While neoclassical tearing modes⁴⁶ usually grow too slowly to be of concern during the initial heating phase and approach to a burning plasma regime, on longer time scales (fractions of the diffusive skin time - for sustained burn regimes) these modes may cause confinement to deteriorate or perhaps cause a major disruption. The value $\beta_n = 1.8$ in ITER-FEAT is slightly lower than the β_n values in present tokamak experiments where neoclassical tearing modes occur. There are some indications however that the critical β_n for the onset of the modes could be lower at the lower values of ρ_* of ITER-FEAT. A possible remedy is to use feedback stabilisation. Since these modes apparently would not influence the approach to a burning plasma regime, but only potentially limit the duration or performance of a burning plasma regime, and since feedback stabilization seems possible, the neoclassical tearing mode issue presently seems like

a tractable one that needs to be addressed carefully, not one that is a substantial threat to the ITER-FEAT mission.

3. Alpha particle physics issues

The next step fusion experiment must have as one of its main scientific goals the study of alpha particle physics. This implies the production of a burning plasma, in which the alpha particles represent the dominant form of heating and the dominant fast ion population. ITER-FEAT has the potential for fulfilling these conditions since $Q \sim 10$ implies $P_\alpha = 2P_{\text{aux}}$ which may fulfil (qualitatively) the notion of being the dominant form of heating.

However, if the auxiliary power is such as to produce significant fast ion populations, these may compete with the alphas in driving collective modes such as fishbones and Toroidal Alfvén Eigenmodes. It would be difficult, in that case, to separate the effect of the alpha particles from that of the other fast ions. This situation would arise with minority ion cyclotron heating (if the minority ion concentration is kept relatively small) and with energetic neutral beam heating. Of course, there are ICRH schemes that will not produce a significant fast ion population, such as resonant tritium absorption in a 50-50 D-T mixture. These are therefore highly recommended in order to avoid this potential difficulty.

3. The consequences of the small scrape off layer thickness on divertor loading is an open issue that must be considered carefully.

IV. CONCLUSIONS AND OPEN ISSUES

Panel members are convinced that magnetic fusion has made significant progress over the years and that, in spite of incomplete understanding, the world fusion program is now in a position to proceed to the design and construction of a burning plasma experiment. Here, a burning plasma is defined as a plasma where the fusion-produced alpha particles are the dominant form of heating. In quantitative terms, this implies values of alpha particle power, P_α , significantly exceeding the input power, which is the sum of ohmic and auxiliary heating powers, $P_{in} = P_{ohm} + P_{aux}$. In terms of the thermonuclear gain parameter, $Q = P_{fus}/P_{in}$, where $P_{fus} = 5P_\alpha$ a fusion burning plasma should have $Q \geq 10$ for periods that are long on the relevant plasma evolution time scales.

The two experiments under consideration, IGNITOR and ITER-FEAT, follow different paths to reach this target and have important differences in their objectives. ITER-FEAT is well capable of reaching $Q=10$ assuming realistic flat density profiles; ignition is not precluded, but would require slightly peaked

density profiles or operation close or beyond operational limits, such as beta, Greenwald density, and enhancement over H-mode confinement. In IGNITOR, the goal of ignition ($Q^* = \infty$) would be reached with a non-stationary stored energy and Q close to 10, provided peaked density profiles, with $n_{e0}/\langle n_e \rangle$ of order two, can be maintained for a few energy confinement times.

The ITER-FEAT design is the result of a broad based effort on the part of the fusion community, while IGNITOR has not enjoyed such a broad based participation, which must be born in mind in any comparison. Successful operation of a plasma confinement experiment such as IGNITOR would greatly benefit in exploring operational modes for eventual operation of a fusion proto-reactor device such as ITER.

A number of open issues apply to IGNITOR and to ITER-FEAT. Hence in the following the two machines are dealt separately. These problems listed below are being addressed with high priority by the international community, but should not be used as an excuse to delay decisions to proceed with the final design and construction of either, or both, of the two experimental programs under consideration.

IGNITOR

Significant progress on the IGNITOR concept has been made recently. Most notably, as compared with previous

versions, the new IGNITOR proposal has increased flexibility by incorporating adequate ICRH power levels and pellet injection in the design. These systems are considered essential in providing a degree of confidence for access to improved confinement regimes. In addition, the poloidal field system now has the capability of producing a variety of equilibrium configurations, including magnetic X-points.

The IGNITOR design does not include a divertor. Consequently, the reference mode of operation is the L-mode. However, an IGNITOR that performed no better than what one projects from the ITER89 L-mode scaling law would be disappointing, as it would reach values of the thermonuclear gain parameter Q not larger than¹⁹ 3. On the other hand, if peaked density profiles in IGNITOR can be produced and maintained, then ignition requires an enhancement between 1.3 and 1.6 relative to L-mode, depending on the degree of profile peakedness. It should be pointed out that profile peaking and enhanced confinement occur together in existing experiments, albeit together with impurity accumulation again degrading the performance. Tokamak operating regimes (other than H-mode) with enhancements of the required magnitude have been observed at least transiently, so that ignition in limiter configurations is a distinct possibility. However, producing and maintaining an adequate density profile in IGNITOR for a

sufficiently long time are still open issues which have to be faced owing to their critical importance for achieving the required performances. Moreover, once these matters are settled, an enhancement confinement factor will still be needed. Although present experiments show that enhancement factors of the required magnitude are obtained in peaked density limiter discharges, the empirical database for extrapolation to ignition has to be developed.

The panel members note that several questions related to IGNITOR performance are still open and require further studies and dedicated experimental campaigns in existing tokamaks. In particular, we offer the following recommendations:

(i) Develop a database for high field, compact (i.e., large B/R) experiments. We expect ENEA to be a prime actor on this, with an aggressive IGNITOR campaign on FTU. Unfortunately, FTU has a circular cross-section; therefore, it cannot address specific questions related to the IGNITOR geometry. Alcator C-MOD may also be in a position to contribute with dedicated experiments. Key questions are whether peaked profiles can be produced and maintained in very high density and high magnetic field experiments, with particular attention to fueling and enhanced confinement possibilities, and whether high purity is maintained with a radiating mantle at the plasma edge, with particular attention to wall power handling issues. The access to

improved confinement regimes of relevance to IGNITOR should be investigated experimentally also in other devices such as JET.

(ii) Perform independent transport calculations with codes such as PRETOR and BALDUR in order to directly compare IGNITOR and ITER-FEAT. Also, these codes should be tested against the available experimental database. Apply first-principle (e.g., gyrokinetic plasma turbulence) codes to investigate relevant transport physics issues. Existing transport codes in Europe and the US should be considered for these tasks.

(iii) Perform computational and experimental pellet penetration studies in IGNITOR-relevant plasma conditions.

(iv) Perform comprehensive MHD stability studies, with special attention to major disruptions, which may limit high field operation at full current. Also, electromechanical effects of disruptions and the production of runaway electrons during disruptions as well as possibly during current ramps need to be assessed.

(v) Proceed with designs of ICRF antennas and high-speed pellet injectors, in order to find out whether prospects for these systems are realistic.

(vi) Clarify diagnostic systems that can be implemented in the IGNITOR machine.

(vii) Begin engineering system integration and detailed industrial cost assessment.

ITER-FEAT

The panel members noted that a significant international effort was set in place in order to clearly define the goals, the physics basis, and the engineering aspects, including costs, of the original ITER-FDR experimental proposal. Even though open problems remained, it was clear that these problems were being addressed with maximum priority by a large section of the international physics community.

The new proposal, ITER-FEAT, represents a scaled-down, reduced-cost version of ITER-FDR. The goals of ITER-FEAT are less ambitious than those of ITER-FDR. This new proposal has been put on the table very recently. It is tempting to say that the physics and engineering considerations that applied to the old proposal are now valid for the new one. However, adequate time should be allowed for a proper reassessment, including dedicated ITER-FEAT demonstration experiments that take into account the modified geometry (different elongation, triangularity, etc.) of the new ITER as compared to the old one.

ITER-FEAT should reach the goal of $Q \sim 10$ in steady state, ELMy H mode operation assuming flat density profiles. The panel is confident that this objective during 400 sec of operation is within reach. Ignition is not precluded; however this requires slightly peaked profiles or an enhancement of 10% over ELMy H-mode scaling predictions or operation at the *I7MA* level close

to beta (MHD) and Greenwald density limits. Thus, the achievement of ignition in ITER-FEAT cannot be expected with the same confidence.

There are three problem areas that have been identified for ITER-FEAT. These must be dealt with in order to allow a proper judgment on the physics factors listed above:

(i) The consequences of the small scrape off layer thickness on divertor loading is an issue that must be considered carefully.

(ii) An experimental demonstration, in existing tokamak devices, on the possibility of avoiding or mitigating monster sawtooth crashes in preferred scenarios must be given, under experimental conditions (i.e. auxiliary power levels, q profiles, confinement regimes and values of relevant dimensionless parameters) as close as possible to those foreseen for ITER-FEAT. These experiments as well as others in the database should be used to calibrate codes based on sawtooth models. Predicted performance in scenarios that safely avoid sawteeth by profile control or by utilising the long skin time should be estimated. We point out that the typical time scale for the monster sawtooth period is estimated to be a few tens of seconds in ITER-FEAT. If the plasma performance is degraded after the first monster sawtooth crash, then the burning plasma phase of the discharges would be significantly limited in time.

(iii) Issues of MHD stability - in particular neoclassical tearing modes and the influence of low plasma toroidal rotation at which ITER-FEAT is expected to operate which could lead to reduced performance - should be explored.

The panel members trust that these problems can be dealt with satisfactorily provided dedicated experimental time is allotted in large-size tokamak devices such as JET and appropriate numerical simulations are performed.

V. RECOMMENDATIONS

Although being both intended to confine and study a burning plasma, the ITER-FEAT and the IGNITOR experiments have not to be considered as competing for the same objectives. The objectives of ITER-FEAT are more far reaching than those of IGNITOR, which explains the difference in cost and construction time of the two machines. The main physics target of ITER-FEAT is to achieve values of $Q \sim 10$ under steady state with respect to the relevant plasma evolution time scales including helium accumulation, albeit only marginally with respect to the global current diffusion time scale. The machine would be pulsed, with discharges lasting approximately one to two global current diffusion times. Ignition in ITER-FEAT is not precluded with slightly more favourable conditions on density profiles or confinement. In addition, ITER-FEAT aims at

addressing reactor-relevant engineering issues. However, since it will take at least twelve years to produce the first burning plasma in ITER-FEAT, it has to be considered as a long-term fusion research objective.

The high field, high-density approach, as defined in the IGNITOR project, is an alternative route to a burning plasma experiment. It separates off the ITER-FEAT line not only by the magnetic field strength, but also by the involved confinement physics, which has to deal with a peaked density profile ($n_{e0}/\langle n_e \rangle \sim 2$), a cold radiating mantle and no divertor system. High values of Q in IGNITOR would be reached transiently over time intervals lasting between five and ten energy confinement times, but shorter than a global current diffusion time. An experiment along these lines would be aimed at exploring the potential of this alternative configuration for providing an expeditious and cost-effective path in which the initial phase of a burning plasma could be studied, without addressing the helium accumulation problem or any reactor-relevant engineering issues.

Consequently, the recommendations stated below will not provide any choice nor provide any comparative assessment between the two projects. They only intend to answer the questions raised in the terms of reference, as recalled at the beginning of the report.

Recommendation 1: *Panel members believe that the ITER-FEAT proposal is sound, has reached maturity and that the plasma performances required for reaching the stated objectives of ITER-FEAT rely on robust extrapolations from validated experimental databases. Panel members believe that the ITER-FEAT proposal will reach its main objectives and will bring an outstanding contribution to a reactor oriented strategy. The remaining issues, although not critical, deserve to be addressed but they must not delay any positive decision concerning the experiment.*

Recommendation 2: *In the near term, an effort should be made to acquire a degree of confidence on the remaining open issues concerning IGNITOR by appropriate R&D, dedicated experiments in existing tokamaks and numerical investigations. Such an experiment would be on the frontier of plasma physics and thus have both risks and opportunities, a feature in common with other great physics experiments.*

Recommendation 3: *Establish an international burning plasma study group.*

A broader scientific dialogue should be encouraged, so as to co-ordinate further the best inputs from the world fusion community, to strengthen common guidelines and methodologies and to build an even broader consensus in support of the international burning plasma experimental program. It is proposed that this task be co-ordinated through an international expert group, and involve a network of participating fusion laboratories and research centres.

Acknowledgements

The authors would like to acknowledge useful discussions with several colleagues, in particular with P. Buratti, B. Coppi, D. Campbell, M. Greenwald, J. Johner, M. Ottaviani, M. N. Rosenbluth, J. Van Dam, and A. Wootton.

¹ ITER-FEAT report presented to the panel.

² B. Coppi, *et al.*, MIT (RLE) Report PTP 99/06 (1999); revised version, February 2000.

³ K. Miyamoto, *Plasma Physics for Nuclear Fusion* (MIT Press, Cambridge, MA, 1989), pp. 8-9.

⁴ B. Coppi, M. Nassi, and L. E. Sugiyama, *Physica Scripta* **45**, 112 (1992).

⁵ B. B. Kadomtsev, *Tokamak Plasma: A Complex Physical System* (IOP, Bristol, 1992).

⁶ M. Greenwald, *et al.*, *Phys. Rev. Lett.* **53**, 352 (1984).

⁷ R. P. Parker, *et al.*, *Nucl. Fusion* **25**, 1127 (1985).

⁸ M. Greenwald, *et al.*, *Phys. Plasmas* **2**, 2308 (1995).

⁹ G. Bracco, *et al.*, in Proc. 21st EPS Conf. in *Plasma Physics and Controlled Fusion* (Montpellier, 1994), p. 70.

¹⁰ M. Bessenrodt-Weberpals, K. McCormick, F.X. Soldner, *et al.*, *Nucl. Fusion* **31**, 155 (1991).

¹¹ B. Coppi and F. Porcelli, *Phys. Rev. Lett.* **57**, 2272 (1986).

-
- ¹² B. Coppi and F. Porcelli, *Fusion Technol.* **13**, 447 (1988).
- ¹³ M.L. Apicella, *et al.*, *Nucl. Fusion* **37**, 381 (1997).
- ¹⁴ G. F. Matthews, *et al.*, *J. Nucl. Mat.* **241-243**, 450 (1997).
- ¹⁵ R. R. Weynants, *et al.*, *Nucl. Fusion* **39**, 1637 (1999).
- ¹⁶ E. Mazzucato, S. H. Batha, M. Beer, M. Bell, *et al.*, *Phys Rev. Lett.* **77**, 3145 (1996).
- ¹⁷ S. M. Kaye and the ITER-FEAT confinement database working group, *Nucl. Fusion* **37**, 1303 (1997).
- ¹⁸ W. Horton, P. Zhu, G. Hoang, T. Aniel, M. Ottaviani, and X. Garbet, *Phys. Plasmas* **7**, 1494-1510 (2000).
- ¹⁹ J. Johner, Preliminary Assessment of IGNITOR Performances, Report EUR-CEA-FC-1694, March 2000.
- ²⁰ B. Coppi and E. Mazzucato, *Phys. Letts. A* **71**, 337 (1979).
- ²¹ Y. Shimomura, JAERI Report JAERI-M 87-080 (1985).
- ²² B. Blackwell *et al.*, *9th Int. Conf on Plasma Physics and Contr. Fusion Research* (Baltimore, 1982) vol. 2 (Vienna, International Atomic Energy Agency) p. 27.
- ²³ M. Z. Tokar, *et al.*, *Plasma Phys. Contr. Fusion* **41**, L9 (1999).
- ²⁴ U. Samm, G. Bertschinger, P. Bogen, *et al.*, *Plasma Phys. Contr. Fusion* **35**, B167 (1993); J. Winter, *et al.*, *Phys. Rev. Lett.* **71**, 1549 (1993).
- ²⁵ W. Horton, *Rev. Mod. Phys.* **71**, 735 (1999).
- ²⁶ B. Coppi and C. Spight, *Phys. Rev. Lett.* **41**, 551 (1978).
- ²⁷ A. M. Messiaen, J. Ongena, U. Samm, *et al.*, *Nucl. Fusion* **36**, 39 (1996).
- ²⁸ K. C. Shaing, *Phys. Fluids* **31**, 2249 (1988).
- ²⁹ G. Becker, *Nucl. Fusion* **30**, 2285 (1990).
- ³⁰ M. Hugon, B.Ph. van Milligen, P. Smeulders, *et al.*, *Nucl. Fusion* **31**, 33 (1992).
- ³¹ See, e.g., H. Weisen, F. Hofmann, *et al.*, *Plasma Phys. Contr. Fusion* **38**, 1137 (1996).
- ³² M. Greenwald, private communication.
- ³³ ITER EDA Agreement and Protocol 1, ITER EDA Documentation Series, No. 21, (IAEA, Vienna, 1998).
- ³⁴ Final Design Report, ITER EDA Documentation Series, (IAEA, Vienna, 1998).
- ³⁵ See the December 1999 Issue of *Nucl. Fusion*, *ITER Physics Basis*, (IAEA, Vienna, 1999).

-
- ³⁶ G. Saibene, R. Budny, A. V. Chankin, et al., *Nucl. Fusion* **39**, 1133 (1999).
- ³⁷ R. La Haye et al., in *Controlled Fusion and Plasma Physics 1997* (Proc. 24th Eur. Conf. Berchtesgaden, 1997), Vol. 21A, Part III, (European Physical Society, Geneva, 1997) 1121-1244.
- ³⁸ M.F.F. Nave, S. Ali-Arshad, B. Alper, et al., *Nucl. Fusion* **35**, 409 (1995).
- ³⁹ G.T.A. Huysmans et al., Proc. 24th EPS Conference on Controlled Fusion and Plasma Physics, Berchtesgaden, June 1997; Part IV, p. 1857.
- ⁴⁰ T.S. Taylor, et al., in *Plasma Physics and Controlled Nuclear Fusion Research 1990* (Proc. 13th Int. Conf. Washington D.C., 1990) vol. 1, IAEA, Vienna (1991) p. 177; Y. Kamada, et al., in *Fusion Energy 1996* (Proc. 16th Int. Conf. Montreal, 1996), vol. 1, IAEA, Vienna (1997) p. 247.
- ⁴¹ Y. Kamada, *Plasma Phys Control. Fusion* **38**, 1173-1188, (1996).
- ⁴² D. J. Campbell, D.F.H. Start, J.A. Wesson, et al., *Phys. Rev. Lett.* **60**, 2148 (1988).
- ⁴³ M. N. Bussac, R. Pellat, D. Edery, and J. L. Soule, *Phys. Rev. Lett.* **35**, 1638 (1975).
- ⁴⁴ H. Lutjens, A. Bondeson, and G. Vlad, *Nucl. Fusion* **35**, 1625 (1992).
- ⁴⁵ F. Porcelli, D. Boucher, and M. N. Rosenbluth, *Plasma Phys. Contr. Fusion* **38**, 2163 (1996).
- ⁴⁶ Z. Chang, et al., *Phys. Rev. Lett.* **74**, 4663 (1995).